

SD SERIES - SPECIFICATION DATA SHEET 2.3



www.kirkkey.com


Luft Brasil Ind. Com. Ltda

R. Dom Andrés Lamas, 56
Tataupé São Paulo - SP
(11) 3795-0000

www.luftbrasil.com.br



Type Thermoplastic Bodied Switch



Thermoplastic bodied electrical contacts offer the best protection against water ingress. These auxiliary contacts are available for five styles of the SD Series interlocks:

- Type F (SD Series Data Sheet 1.1)
- Type B (SD Series Data Sheet 1.2)
- Type T (SD Series Data Sheet 1.3)
- Type D (SD Series Data Sheet 1.4)
- Type FN (SD Series Data Sheet 1.7)

The contacts can be used to provide remote indication of the lock bolt position or to switch control circuitry.

The contacts respond directly to the movement of the locking bolt when the key is turned. Option A comes with 2 N/O & 1 N/C 5 amp contacts (locking bolt withdrawn). Option B comes with 4 N/O & 2 N/C 5 amp contacts (locking bolt withdrawn). The contacts change state when the key is turned and the locking bolt is extended.

To order the auxiliary contact option, put "A" or "B" in column four of the interlock part number. Reference the SD Series Ordering Guide and the drawing on page 3.



www.kirkkey.com


Luft Brasil Ind. Com. Ltda

R. Dom Andrés Lamas, 56
Tataupé São Paulo - SP
(11) 3795-0000

www.luftbrasil.com.br



Type Thermoplastic Bodied Switch



OPTIONS

- Standards: VDE 0660 T200, DIN EN 60947-5-1, IEC 60947-5-1.
- Utilization Category: AC-15, Ue/Ie 240V/1,5A.
- Approvals: cCSAus B300 (same polarity).
- Enclosure & Cover: Thermoplastic, glass fibre reinforced (UL 94-V0).
- Hinged Snap Lid: For quick and easy access (screwdriver release). Lid hinges open to 135 degrees.
- Forced Disconnection of NC Contacts: To IEC/EN 60947-5-1, Annex K.
- Temperature Range: -30 degrees C (ice free) to +80 degrees C.
- Mechanical Lifecycle: 200,000 operations.
- Screw Terminals: Self-lifting clamps for easy wiring, Numbered in accordance with DIN EN 50013.
- Ingress Protection: IP65 acc. to EN 60529.
- Rated Insulation Voltage: 250V AC.
- Rated Operational Voltage: 240V.
- Continuous Thermal Current: 5 Amp.
- Cable Entrance: M20 x 1.5 thread. The switch is supplied with .20 -.35" cable gland installed. An M20 x 1/2" FIP adapter is supplied with each switch for use with 1/2" conduit.
- EU Conformity: CE Marked
- Weight: The A Option adds 9.6oz / 272g and the B Options adds 16oz / 453g to the weight of an interlock.

SD SERIES - SPECIFICATION DATA SHEET 2.3



www.kirkkey.com

Luft Brasil Ind. Com. Ltda

R. Dom Andrés Lamas, 56
Tataupé São Paulo - SP
(11) 3795-0000

www.luftbrasil.com.br



Type Thermoplastic Bodied Switch

